

## AHEAD-2.0L

## The "state of the art" of tissue technology.

AHEAD-2.0L represents the "state of the art" of Toscotec technology. It is a high performance tissue machine with with a gross production of 225 tpd and an operating speed up to 2000 mpm.

Thanks to the high level of customization of this unit (multilayer headbox, Steel Yankee Dryer TT SYD with diameter ranging from 16' (4876) to 22' (6705 mm), TT SuctionPressRoll, the Pope reel with spool drive assist), AHEAD-2.0L is the right solution for all those markets where productivity, quality of finished products, flexibility and

energy savings are a "must".

The AHEAD-2.0L standard unit consists of a five roll cantilevered Crescent Former with a Ø 1540 mm forming roll, a multilayered headbox (TT Headbox-MLT), an hydraulically loaded cantilevered press section TT SuctionPressRoll-SPR1200, Ø 825 mm rolls, a Steel Yankee Dryer TT SYD-16FT (4876 mm) working at max 10 bar(g), hydraulic Pope reel type TT Reel-H with max reel diameter up to 3000 mm and a Duo-system gas fired hood by Milltech. An alternative upgraded solution of AHEAD-2.0L can include the multilayered headbox

(TT Headbox-MLT) with Dilution System option, the hydraulically loaded large diameter press roll TT SuctionPressRoll-SPR1425, an advanced hydraulic Pope reel type TT Reel-H+ featuring linear secondary arms, spool drive assist and enhanced automatic reel spools magazine.

Authomatic shaft puller installation for jumbo rolls is available too.

A design with two presses solution upgraded with ultimate Toscotec Shoe Press TT XPress could be installed.

Also we offer solutions with larger Steel Yankee Dryer TT SYD-18FT, 20FT, 22FT and Steam Heated Hood.


## Benefits


- High Performance
- Top Quality Technology
- Energy Saving\*
- Maintenance and Easy Operations
- High Custom-Tailoring



\*Every Toscotec system delivers maximum energy efficiency with minimum environmental impact.







AHEAD-2.0L	
Net sheet width	Up to 5600 mm (220.5 inch)
Basis weight on reel	12-40 g/m²
Crepe	10-25%
Design speed	2200 mpm
Max operating speed	2000 mpm
Max daily production	Up to 240* tpd
Yankee diameter	TT SYD-16FT (4876 mm)

<sup>\*</sup>referred to a single press configuration. Other different design configuratios are available.