



TOSCOTEC CRESCENT FORMER LINES FOR TISSUE
Solutions for every customer's needs.



THE GOAL: TO OFFER HIGHLY SPECIALIZED AND CUSTOMIZED TECHNOLOGY SOLUTIONS COVERING THE WIDEST RANGE OF GRADES AND PRODUCTION CAPACITIES.

THE SOLUTIONS: MODULO AND AHEAD, THE TOSCOTEC TISSUE LINES.

■ **MODULO: compact, modular tissue machines.**

The possibility to install the pre-assembled sections of the tissue machines on site reducing transportation costs and erection time is the innovative MODULO concept. This concept is extended to the whole plant engineering including auxiliary components and stock preparation system.

MODULO LINE is proposed for a daily production up to 75 tpd and can be supplied with a complete package of auxiliary plants for a "turn-key" solution.

■ **AHEAD: high speed tissue machines.**

Thanks to their flexible design, all the models for the AHEAD range may be customized in order to comply with the broadest requirements of production both for raw materials and for quality of finished products.

Great care was used in the development of a wide range of solutions designed to increase the efficiency and runnability of AHEAD machines as well as to optimize accessibility of the units to minimize maintenance activities.

Each AHEAD model may be equipped with all the necessary accessory plants for a "turn-key" supply, including stock preparation systems and related rewinders.

MODULO TISSUE LINE

MODULO

- Net sheet width: 2850 mm (112 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-3200MM
- Max operating speed: 1000 mpm
- Max drying capacity: up to 50* tpd



MODULO-PLUS

- Net sheet width: 2850 mm (112 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-12FT
- Max operating speed: 1500 mpm
- Max drying capacity: up to 75* tpd



AHEAD TISSUE LINE

AHEAD-1.5S

- Net sheet width: 2850 mm (112 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-12FT
- Max operating speed: 1800 mpm
- Max drying capacity: up to 90* tpd



AHEAD-1.5M

- Net sheet width: 3600 mm (141.7 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-12FT
- Max operating speed: 1600 mpm
- Max drying capacity: up to 105* tpd



AHEAD-2.0S

- Net sheet width: 2850 mm (112 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-15FT
- Max operating speed: 2000 mpm
- Max drying capacity: up to 120* tpd



AHEAD-2.0M

- Net sheet width: 3600 mm (141.7 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-15FT
- Max operating speed: 2000 mpm
- Max drying capacity: up to 145* tpd



AHEAD-2.0L

- Net sheet width: 5600 mm (220.5 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-16FT
- Max operating speed: 2000 mpm
- Max drying capacity: up to 240* tpd



AHEAD-2.0L PRODERGY

- Net sheet width: up to 5600 mm (220.5 inch)
- Basis weight on reel: 12-40 g/m²
- Crepe: 10-25%
- Yankee size: TT SYD-22FT
- Hood type: TT Milltech-DYH fed by Steam
- Max operating speed: 2000 mpm
- Max drying capacity: up to 240 tpd



* referred to a single press configuration. Other different design configurations are available.

ITALY

Toscotec S.p.A.
Viale Europa, 317/F
55012 Marlia, Lucca, Italia

NORTH AMERICA

Toscotec North America
3313 S. Packerland Drive
De Pere, WI 54115, USA

ASIA & PACIFIC

Toscotec Paper Machine (Shanghai) Co., Ltd.
598, Heng'An Road, Gaohang
200137 Shanghai, PR China

www.toscotec.com